

Benchtop Low Speed Centrifuge BLC-3200



Description

Benchtop Low Speed Centrifuge BLC-3200 with lock function, self-diagnostic function, and Automatic identification system for magnetic rotor, automatic matching of corresponding rotor program, preventing misoperation and ensuring centrifugal safety.

Suitable for clinical medicine, biochemistry, genetic engineering, immunological applications. Features with 7-inch touch screen with multi-functional knob combination parameters. Accommodates angle, swing rotor and swing rotor as these motor capable of accommodating a great number of tubes at once.

Specifications:

Model	BLC-3200
Capacity	4×750 ml
Max RCF	5190×g
Speed Range	6500 rpm
Noise	?60dB?A?
Rotor	Angle rotor 1 : 6×50ml, 12×10ml; 6500 rpm, 5190×g Swing out 2: 4×50ml(option); 4000 rpm, 2810×g
Rotor Diameter	430 mm
Revolutions/min	±10 rpm
Timer	1min to 99h, 59min, 59s
Power Consumption	750 W
Dimension	560×460×390 mm
Packing Dimension	637×537×484 mm
Net Weight	58 kg
Electrical Requirement	AC 220±22V/50Hz 15A
Catalogue No.	1401000502

Technical:

Model	BLC-3200
Capacity	4×750 ml
Max RCF	5190×g
Speed Range	6500 rpm
Noise	?60dB?A?
Rotor	Angle rotor 1 : 6×50ml, 12×10ml; 6500 rpm, 5190×g Swing out 2: 4×50ml(option); 4000 rpm, 2810×g
Rotor Diameter	430 mm
Revolutions/min	±10 rpm
Timer	1min to 99h, 59min, 59s
Power Consumption	750 W
Dimension	560×460×390 mm
Packing Dimension	637×537×484 mm
Net Weight	58 kg
Electrical Requirement	AC 220±22V/50Hz 15A
Catalogue No.	1401000502

Shipping: BIOLAB SYSTEMS	2 - 3 weeks Delivery.
speed:	6500 rpm
maximum_temperature:	-
power:	750 W
capacity:	4750 ml
model:	BLC-3200

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States