

Benchtop Large Capacity Refrigerated



Description

Benchtop Large Capacity Refrigerated Centrifuge DBLC-2080 compiled with microcomputer allow for instant rotor identification, which robotically converts the rotational speed to the relevant RCF checking the user from setting a speed above the capabilities of the installed rotor along with R404a compressor unit and are convenient for a wide range of applications.

Features with LCD/LED touch screen with multi-functional knob combination parameters. Accommodates different rotor and adaptors, as these motor capable of accommodating a great number of tubes at once. Available with 9 profiles for acceleration and for deceleration with high efficiency. Additionally, it comes with DC brushless converter motor.

Specifications:

Model	DBLC-2080
Capacity	250mlx4
Max RCF	9100xg
Speed Range	8000 rpm
Noise	<65dB(A)
Temperature Range	-5 to +35?
Revolutions/min	± 30 rpm
Temperature Accuracy	±1?
Timer	1 to 99min
Dimension	460x710x420 mm
Packing Dimension	580x730x520 mm
Weight	80 kg
Electrical Requirement	220V/60Hz 5A
Catalogue No.	1401351002

Technical:

Model	BLC-2050		BLC-2080	
Capacity	15mlx32		250mlx4	
Max RCF	4390xg		9100xg	
Speed Range	5000 rpm		8000 rpm	
Noise	<65dB(A)			
Temperature Range	-5 to +35?			
Revolutions/min	± 30 rpm			
Temperature Accuracy	±1?			
Timer	1 to 99min			
Dimension	460x710x420 mm			
Packing Dimension	580x730x520 mm			
Weight	80 kg			
Electrical Requirement	AC110/50Hz, 5A	220V/60Hz 5A	AC110/50Hz, 5A	220V/60Hz 5A
Catalogue No.	1401350501	1401350502	1401351001	1401351002

Shipping:	2 - 3 weeks Delivery.
speed:	8000 rpm

maximum_temperature:	-5 to +35?
power:	-
capacity:	250mlx4
model:	DBLC-2080

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States