

Floor Standing Large Capacity



Description

Floor Standing Large Capacity Refrigerated Centrifuge FLRC-5000 designed for the pharmaceutical and biological products. The angle rotor and swing rotor are available for separation of cells suspension. This versatile and reliable centrifuge is used for high-throughput clinical, medical and research applications.

There are 9 profiles available for acceleration and 9 for deceleration; user can select these profiles by the main display and worked with temperature up to -20 to 40°C.

Featuring with LCD display with dual synchronous display screen and design with double lock door, electric door with magnetic locks, to provide more protection and safety and adaptors as optional accessories. Driven by a microprocessor, AC frequency conversion motor drive, and quiet operation clean.

Specifications:

Model	FLRC-5000
Capacity	6x2400 ml
Max RCF	12166xg
Speed Range	7200 rpm
Noise	<62dB(A)
Temperature Range	-20 to 40°C
Revolutions/min	±30 rpm
Temperature Accuracy	±2°C
Timer	1 to 99min,59sec
Power Consumption	7500 W
Dimension	870x1020x970 mm
Weight	545 kg
Electrical Requirement	AC220V/50Hz,60Hz, 50A
Catalogue No.	1402600502

Technical:

Model	FLRC-5000
Capacity	6x2400 ml
Max RCF	12166xg
Speed Range	7200 rpm
Noise	<62dB(A)
Temperature Range	-20 to 40°C
Revolutions/min	±30 rpm
Temperature Accuracy	±2°C
Timer	1 to 99min,59sec
Power Consumption	7500 W
Dimension	870x1020x970 mm
Weight	545 kg
Electrical Requirement	AC220V/50Hz,60Hz, 50A
Catalogue No.	1402600502

Shipping:	2 - 3 weeks Delivery.
------------------	-----------------------

speed:	7200 rpm
maximum_temperature:	-20 to 40C
power:	7500w
capacity:	6x2400 ml
model:	FLRC-5000

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States