

Gel Documentation System GS-2010



Description

Gel Documentation System GS-2010 covers chemiluminescence and multiplexing fluorescence applications. Ideal for reproducible and comparable quantification data. Add a UV transmission, UV+BLUE light transmission, UV+BLUE+White light transmission, and UV+BLUE+White transmission and RGB reflection.

The scientific CCD camera is controllable from PC., operation mode convertor, multi fluorescence mode, ultra-slim transilluminator for blue light and white light transmission, and UV transilluminator contain a non-lamp design for uniform transmission.

Applicable for blotting membrane such as western lightning, ECL, ECL plus, CDP star, super signal, CSPD, LumiGlo, Cy2, Cy3, Cy5, FITC, Alexa dyes, daylight dyes, ProQDiamond, ProQEmerald 300, ProQEmerald 488, IR Dye 680, etc.; protein inspection and Gel Inspection. The system is built for high performance and automation and features a next-generation, and compatible with 8 Sockets filter wheel. Build-in software for image enhancement, editing, and image analysis. Detect far weaker signal and offer higher sensitivity and wider linear range, human-computer interactive program.

Technical:

Model	GS-2010	GS-2020	GS-2030
Lens	F0.8 motorized ultrafast	F0.95 motorized ultrafast	F0.8 motorized ultrafast
Type	-	Embedded industry computer with touch screen	
Sensor	12.49x9.99 mm CCD sensor		
Camera	CCD camera		
Resolution	6.05 MP, 2750x2200		
Efficiency	?75%		
Pixel Size	4.54x4.54 μm		
Pixel Density	16 bit(65536 gray scale)		
Filter Wheel	8 sockets filter wheel		
Cooling Temperature	25°C		
Excitation Light	UV Light Ex365, Blue Light Ex470, Green Light Ex530, Red Light Ex630, Near infrared Ex660, Near infrared Ex770		
Filters	Em460/30F, Em460/31F, Em460/32F, Em460/33F, Em460/34F, Em460/35F		
Internal Dimension	430x380x690 mm		
External Dimension	550x490x760 mm		
Weight	33 kg		
Electrical Requirement			
Catalogue No.	3403005-04	3403010-04	3403015-04

Shipping:	2 - 3 weeks Delivery.
cooling_temperature:	25C
filter_wheel:	8 sockets filter wheel
efficiency:	-
camera:	CCD camera
lens:	F0.8 motorized ultrafast
design_type:	-

intensity:	-
UV Shield:	-
filter_size:	-
resolution:	6.05 MP, 27502200
wavelength:	-
model:	GS-2010

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States