

Medical Refrigerator 2 to 20°C UMR-1310



Description

Medical Refrigerator 2 to 20°C UMR-1000 embedded with evaporator copper tube in a foam layer to prevent corrosion, to ensure heat transferring efficiency and glass door, different designed compact finned condenser for better efficiency. The maximum capacities of 317 L and defrost automatically. Build-in inner fan-driven and forced-draft air circulation system provides excellent temperature uniformity. Build-in microprocessor controller to certify tolerances of internal temperatures. Equipped with buzzer and flashing lights, power failure alarm, doors open alarm, high and low-temperature alarm.

Technical:

Model	UMR-1310
Capacity	317 L
Cabinet Type	Upright
Temperature Resolution	0.1°C
Temperature Range	2 to 20°C
Alarms	Power failure alarm, Temperature sensor failure alarm, High / Low temperature alarm, Door open alarm
Refrigerant	Non HCFC
Material	White plastic coated galvanised steel
Shelves	5
Internal Dimension	540 x 425 x 1380 mm
External Dimension	640 x 582 x 1880 mm
Weight	92.5 kg
Electrical Requirement	AC220 V/ 50Hz
Catalogue No.	500250502

Shipping:	2 - 3 weeks Delivery.
refrigerant:	Non HCFC
defrosting:	-
model_type:	Upright
power:	-
temperature_range:	2 to 20C
capacity:	317 L
model:	UMR-1310

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States