

Ultra-Low Upright Freezers -86? UUF-2650



Description

Ultra-Low Upright Freezers -86? UUF-2650 design with cascade refrigeration system that uses two kinds of refrigerants having different boiling points, which run through their own independent freezing cycle and are joined by a heat exchanger.

Features with filter for easy cleaning and single hand openable, Gasket heating, leveling caster, etc. Available with maximum capacity up to 560L with temperature range of -50 to-86°C.

Technical:

Model	UUF-2390	UUF-2490	UUF-2650
Capacity	390 L	490 L	650 L
Temperature Range	-50 to-86°C		
Materials	Outer: White plastic coated galvanised steel; inner: stainless steel		
Alarms	High condenser temperature alarm, power failure, temperature sensor, low battery, high and low temperature alarm, door open alarm		
Type	Upright		
Display	Touch screen		
Refrigerant	Non HCFC		
Shelves	3		
Casters	4		
Certification	CE		
Power Consumption	1300 W		
Internal Dimension	909 x 797 x 1990 mm	589 x 637 x 1310 mm	780 x 637 x 1310 mm
External Dimension	589 x 505 x 1310 mm	900 x 929 x 1990 mm	1091 x 929 x 1990 mm
Weight	283 kg	325 kg	354 kg
Electrical Requirement	AC220 / 50Hz		
Catalogue No.	500650502	500651002	500651502

Shipping:	2 - 3 weeks Delivery.
refrigerant:	Non HCFC
defrosting:	-
model_type:	Upright
power:	1300 W
temperature_range:	-50 to-86C
capacity:	650 L
model:	UUF-2650

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States