

Overhead Stirrers OS-1300



Description

Overhead Stirrers OS-1300 suitable for all kinds of conventional mixing applications. The simple and intuitive operation can significantly improve the work efficiency in the laboratory.

Technical:

Model	OS-1100		OS-1200		OS-1300		OS-1400	
Display / Control Mode	Scale Display / Knob Control		LED Display / Knob Control		LED Display / Touch Control		LCD Display / Touch Control	
Speed Accuracy (rpm)	-		± 1		± 1		± 1	
Speed Range(rpm)	40~2000		40~2000		40~2000		20~2000	
Maximum Viscosity (cps)	20000 cps		20000		20000		20000	
Maximum Torque (N-cm)	70		70		70		70	
Maximum Capacity (L)	20		20		20		20	
Maximum clamping stirrer diameter (mm)	10		10		10			
Clockwise and Counter Clockwise Mixing	Yes		No		Yes		Yes	
Input / Output Power (W)	70 / 50		70 / 50		70 / 50		70 / 50	
Dimensions (W x L x H in mm)	105 x 160 x 185		105 x 160 x 185		105 x 160 x 185		105 x 160 x 185	
Electrical Requirements	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz
Catalogue No.	600100501	600100502	600101001	600101002	600101501	600101502	600102001	600102002

Shipping:	2 - 3 weeks Delivery.
liquid_temperature_range:	-
plate_temperature_range:	-
maximum_viscosity:	20000 cps

speed:	40 - 2000 rpm
power:	150W
capacity:	20 L
model:	OS-1300

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States