

Overhead Stirrers OS-2200



Description

The Overhead Stirrers OS-2200 smart laboratory companions which give you complete control over complex stirring processes. It has a speed range of up to 3000 rpm.

Technical:

Model	OS-2100		OS-2200		OS-2300	
Display/ Control Mode	LED Digital Display / On-Touch Control		LED Digital Display / On-Touch Control		LED Digital Display / On-Touch Control	
Speed Accuracy (rpm)	± 1		± 1		± 1	
Torque Accuracy	± 5%		± 5%		± 5%	
Speed Range (rpm)	Low: 20~600 / High: 600~3000		Low: 12~360 / High: 360~1800		Low: 40~1200 / High: 1200~6000	
Corresponding Torque (N-cm)	Low: 339 / High: 68		Low: 565 / High: 113		Low: 170 / High: 34	
Maximum Viscosity (cps)	100,000		150,000		70,000	
Maximum Torque (N-cm)	339		565		170	
Maximum Capacity (L)	40		40		40	
Output Power (W)	150		150		150	
Dimensions (W x L x H in mm)	200 x 95 x 230		200 x 95 x 230		200 x 95 x 230	
Net Weight (kg)	5		5		5	
Electrical Requirements	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz
Catalogue No.	600102501	600102502	600103001	600103002	600103501	600103502

Shipping:	2 - 3 weeks Delivery.
liquid_temperature_range:	-
plate_temperature_range:	-
maximum_viscosity:	150000 cps
speed:	Low: 12-360 /High: 360-1800
power:	150W
capacity:	-
model:	OS-2200

Iris Analytical Ltd.

**BIOLAB
SYSTEMS**

66 W Flagler St #900

Miami, Florida 33130

United States