

# Digital Viscosity Meter VM-910



## Description

Digital Viscometer VM-910 is used to measure the viscosity of fluid with accurate viscosity reading in products such as paints, coatings, cosmetics, inks, paper pulp, food, oil, starch, solvent-based glue, latex, and other biochemical products, and as asphalt, wax, hot melt adhesives, etc.(high-temperature).

## Technical:

Model No.	VM-910	VM-920	VM-930	VM-940				
Measuring Range	1 to 100000 mPa S		1 to 2000000	1 to 6000000				
Speed	3, 6, 12, 30, 60 rpm		0.3, 0.6, 1. 3, 6, 12, 30, 60 rpm	0.1, 0.3, 0.6, 1.5, 3, 6, 12, 30, 60 rpm				
Measurement error	±1%	±0.5%	±1%	±1%				
Repeatability error	±0.5%	±0.25%	±0.5%	±0.5%				
Display	5 inch color touch-screen							
Rotor	1-4 rotors ( Standard ) ; 0 rotors ( optional )							
Interface	Temperature Probe							
Dimension	350x350x450 mm							
Weight	7 kg							
Electrical Requirement	110V / 60Hz	220V / 50Hz	110V / 60Hz	220V / 50Hz	110V / 60Hz	220V / 50Hz	110V / 60Hz	220V / 50Hz
Catalogue No	650450501	650450502	650451001	650451002	650451501	650451502	650452001	650452002

<b>Shipping:</b>	2 - 3 weeks Delivery.
<b>speed:</b>	3, 6, 12, 30, 60 rpm
<b>reproducibility:</b>	-
<b>measurement_range:</b>	1 to 100000 mPa S
<b>temperature_range:</b>	-
<b>model:</b>	VM-910

## **Iris Analytical Ltd.**

66 W Flagler St #900  
Miami, Florida 33130  
United States