

Touch-Screen Analytical Balances 0.1mg



Description

Touch-Screen Analytical Balances 0.1mg BA-1150T Series feature weighing capacities of 120 g and readabilities of 0.1 mg. Our Analytical Balances are designed with for pharmaceutical, laboratory and regulated weighing in a variety of cell and tissue culture facilities that require the highest accuracy in analytical weighing processes.

Denver Analytical Balances are designed for routine weighing applications in your workplace, offering accuracy and repeatability during essential weighing applications in education, laboratory and, industrial sector. Denver analytical balances deliver competitive performance at an economical price, featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, these balances are perfectly designed for your workplace.

Standard features include Basic functionality for routine weighing applications. Denver analytical balances are equipped with three essential weighing modes, RS232 connectivity for data transfer and storage and internal calibration (in selected models) making them ideal for routine weighing applications.

Designed for uncomplicated operation with easy-to-use display and interface Equipped with an easy-to-read, bright backlit display and a simple user interface, they are incredBTy easy to operate, with almost no training required.

Smart design and durable construction Denver analytical balances have a small footprint which saves on benchtop space while providing a large weighing surface. They are durably constructed, and feature a stainless-steel pan to withstand day-to-day use in the workplace.

Technical:

Model	BA-1050T	BA-1150T	BA-1250T	BA-1350T	BA-1450T	BA-1550T	BA-1650T	BA-1850T	BA-1950T	
Capacity	0 to 100 g	0 to 120 g	0 to 160 g	0 to 180 g	0 to 200 g	0 to 210 g	0 to 220g	0 to 310 g	0 to 320 g	
Display	LCD									
Resolution	0.1 mg									
Pan Dimension	80 mm									
Material	Aluminum alloy die cast base; pan-stainless steel									
Linearity	±0.2 mg									
Calibration	Internal									
Measuring Parameters	g/mg/ct/oz									
Interface	RS232C									
Certification	CE									

ion																		
Stabilization Time	3-5 seconds																	
Dimension	340x2150x350 mm																	
Weight	68 kg																	
Electrical Requirement	AC1 10V	240 V	AC1 10V	240 V	AC1 10V	240 V	AC1 10V	240 V	AC1 10V	240 V	AC1 10V	240V	AC1 10V	240V	AC1 10V	240V	AC1 10V	240V
Catalogue No.	680100501	680100502	680101001	680101002	680101501	680101502	680102001	680102002	680102501	680102502	680103001	680103002	680103501	680103502	680104001	680104002	680104501	680104502

Shipping:	2 - 3 weeks Delivery.
pan_dimension:	80 mm
calibration:	Internal
reproducibility:	-
resolution:	0.1 mg
capacity:	0 to 120 g
model:	BA-1150T

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States