

Top-loading Balances BT-6004S



Description

Top-loading Balances BT-6004S feature weighing capacities of 10 kg, and readabilities of 0.1g. Some applications include weighing, counting, check weighing, weighing under unstable conditions, peek hold and percentage (%).

Denver top-loading balances are designed for routine weighing applications in your workplace, offering accuracy and repeatability during essential weighing applications in education, laboratory and, industrial sector. It delivers competitive performance at an economical price, featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, these balances are perfectly designed for your workplace.

Standard features include Basic functionality for routine weighing applications. Equipped with three essential weighing modes, RS232 connectivity for data transfer and storage and internal calibration (in selected models) making them ideal for routine weighing applications.

Designed for uncomplicated operation with easy-to-use display and interface Equipped with an easy-to-read, bright backlit display and a simple user interface, they are incredBTy easy to operate, with almost no training required.

Smart design and durable construction Denver top pan balances have a small footprint which saves on benchtop space while providing a large weighing surface. They are durably constructed, and feature a stainless-steel pan to withstand day-to-day use in the workplace.

Technical:

| | | | | | | | | | | | | | |
|------------------------|---------------------------------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|--|
| Model | BT-6001S | | BT-6002S | | BT-6004S | | BT-6006S | | BT-6008S | | BT-6010S | | |
| Capacity | 6000 g | | 8000 g | | 10 kg | | 15 kg | | 20 kg | | 30 kg | | |
| Display | LCD | | | | | | | | | | | | |
| Readability | 0.1 g | | | | | | | | | | | | |
| Pan Dimension | 255x190 mm | | | | | | | | | | | | |
| Function | Unit Transforms, Counting, Percentage | | | | | | | | | | | | |
| Interface | RS232 | | | | | | | | | | | | |
| Certification | | | | | | | | | | | | | |
| Packing Dimension | 350x290x160 mm | | | | | | | | | | | | |
| Gross Weight | 4 kg | | | | | | | | | | | | |
| Electrical Requirement | 220V | 110V | 220V | 110V | 220V | 110V | 220V | 110V | 220V | 110V | 220V | 110V | |
| Catalogue No. | 6801350502 | 6801350501 | 6801351002 | 6801351001 | 6801351502 | 6801351501 | 6801352002 | 6801352001 | 6801352502 | 6801352501 | 6801353002 | 6801353001 | |

| | |
|-------------------------|-----------------------|
| Shipping: | 2 - 3 weeks Delivery. |
| pan_dimension: | 255x190 mm |
| calibration: | - |
| reproducibility: | 0.1g |

| | |
|--------------------|----------|
| resolution: | - |
| capacity: | 10 kg |
| model: | BT-6004S |

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States