

Top-loading Balances BT-6010S



Description

Top-loading Balances BT-6010S feature weighing capacities of 30 kg, and readabilities of 0.1g. Some applications include weighing, counting, check weighing, weighing under unstable conditions, peak hold and percentage (%).

Denver top-loading balances are designed for routine weighing applications in your workplace, offering accuracy and repeatability during essential weighing applications in education, laboratory and, industrial sector. It delivers competitive performance at an economical price, featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, these balances are perfectly designed for your workplace.

Standard features include Basic functionality for routine weighing applications. Equipped with three essential weighing modes, RS232 connectivity for data transfer and storage and internal calibration (in selected models) making them ideal for routine weighing applications.

Designed for uncomplicated operation with easy-to-use display and interface Equipped with an easy-to-read, bright backlit display and a simple user interface, they are incredibly easy to operate, with almost no training required.

Smart design and durable construction Denver top pan balances have a small footprint which saves on benchtop space while providing a large weighing surface. They are durably constructed, and feature a stainless-steel pan to withstand day-to-day use in the workplace.

Technical:

Model	BT-6001S		BT-6002S		BT-6004S		BT-6006S		BT-6008S		BT-6010S		
Capacity	6000 g		8000 g		10 kg		15 kg		20 kg		30 kg		
Display	LCD												
Readability	0.1 g												
Pan Dimension	255x190 mm												
Function	Unit Transforms, Counting, Percentage												
Interface	RS232												
Certification													
Packing Dimension	350x290x160 mm												
Gross Weight	4 kg												
Electrical Requirement	220V	110V	220V	110V	220V	110V	220V	110V	220V	110V	220V	110V	
Catalogue No.	6801350502	6801350501	6801351002	6801351001	6801351502	6801351501	6801352002	6801352001	6801352502	6801352501	6801353002	6801353001	

Shipping:	2 - 3 weeks Delivery.
pan_dimension:	255x190 mm
calibration:	-
reproducibility:	0.1g

resolution:	-
capacity:	30 kg
model:	BT-6010S

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States