

Moisture Balance BM-2000



Description

Moisture Balance BM-2000 measures moisture content with increased precision and efficiency with halogen-infrared heat source features, PT100 sensor to ensure process repeatability and wide data storage capacity along with LCD to display time, temperature and weighing results all at a time.

Application area including biology, food, agriculture, pharmacy, textile, dye and research industries to resolve moisture content in a product. A single 400 W halogen lamp heats samples at 1 °C selectable rises. Equipped with color keys to enable quick recognition. Temperature range 5 to 35? and have capacity to weigh up to about 110 g with readability 1 mg.

Iris moisture balance is perfect for measuring moisture in most products including grains, pharmaceuticals, soils, sludge and chemicals. The amount of moisture in a product can greatly affect perceived quality. This measurement is key in quality control process of material as it qualifies quality or purity of a product.

There are different types of heating elements to be considered: ceramic, halogen and quartz elements. Each element offers heating properties so you should consider your application before choosing the appropriate one. Our tech support team can help you to select the relevant model.

The principle of moisture balance is to measure the original weight of a product before the drying process. It automatically and simultaneously dries and weighs solid samples for the determination of moisture content. It provides a continuous direct readout for both weight and percentage moisture loss through the entire cycle

In research work, manufacturing and quality control applications it is essential to be able to determine moisture content simply and reliably. This moisture balances do precisely that, providing moisture content data as a percentage of the initial mass or the residual dry mass.

Technical:

Model	BM-2000	
Capacity	110 g	
Moisture Range	0.00 to 100 %	
Operating Temperature	5 to 35?	
Temperature Range	40 to 199?	
Dry Residual	100 to 0.00 %	
Resolution	1 mg	
Moisture Readability	0.01%	
Dry Residual Readability	0.01%	
Display	Backlight LCD	
Heat Source	1-Halogen Lamp	
Pan Dimension	90 mm	
Sensor	PT-100	
Temperature Step	1?	
Auto stop	0.1 to 9.9% within 1 minute	
ATRO	100 to 999 %	
ATRO	0 to 999 %	
No. of Storage Data	15	
Certification	CE certified	
Time Range	1 to 99 min by 1 sec step	
Power Consumption	400 W	
Dimension	490×360×350 mm	
Weight	7.5 kg	
Electrical Requirement of Balance	220V/50Hz, ±15% ,	115V, ±15
Catalogue No.	6801450501	6801450502

Shipping:

2 - 3 weeks Delivery.

pan_dimension:	90 mm
calibration:	-
reproducibility:	-
resolution:	1 mg
capacity:	110 g
model:	BM-2000

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States