Precision Balances 0.01g BP-3400

Description

Precision Balances 0.01g BP-3400 feature weighing capacities of 4100 g and readabilities of 0.01g. Our Precision Balances are designed for pharmaceutical, laboratory and regulated weighing in a variety of cell and tissue culture facilities that require the highest accuracy in precision weighing processes.
Denver precision balances are designed for routine weighing applications in your workplace, offering accuracy and repeatability during essential weighing applications in education, laboratory and, industrial sector. Denver precision balances deliver competitive performance at an economical price, featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, these balances are perfectly designed for your workplace.
Standard features include Basic functionality for routine weighing applications. Denver precision balances feature three essential weighing modes, RS232 connectivity for data transfer and storage and internal calibration (in selected models) making them ideal for routine weighing applications.
Designed for uncomplicated operation with easy-to-use display and interface Equipped with an easy-to-read, bright backlit display and a simple user interface, they are incredBTy easy to operate, with almost no training required.
Smart design and durable construction Denver precision balances have a small footprint which saves on benchtop space while providing a large weighing surface. They are durably constructed, and feature a stainless-steel pan to withstand day-to-day use in the workplace.

Technical:

Model	BP-3100	BP-3200	BP-3300	BP-3400	BP-3500	BP-3600
Capacity	1100 g	2100 g	3100 g	4100 g	5100 g	6100 g
Repeatability	± 0.02 g				± 0.03 g	
Display	LCD display with backlight					
Resolution	0.01 g					
Pan Dimension	160 mm					
Material	Cast aluminum, static resistant ABS, static-resistant doors (1mg models), stainless steel pan					
Linearity	± 0.02 g				± 0.03 g	
Calibration	Calibration with External Weight					
Measuring Parameters	g, ct, lb, oz, ozt, dwt, etc					
Working Temperature	5 °C to 35 °C					
Interface	Configurable RS 232					
Certification	FCC, CE					
Stabilization Time	? 3 sec					
Dimension	325x205x110 mm					

Electrical Requirement	110V	240V	110V	240V	110V	240V	110V	240V	110V	240V	110V	240V	

Catalogue No.	680650501	680650502	680651001	680651002	680651501	680651502	680652001	680652002	680652501	680652502	680653001	680653002

Shipping:	2 - 3 weeks Delivery.
pan_dimension:	160 mm
calibration:	Calibration with External Weight
reproducibility:	0.02 g
resolution:	0.01 g
capacity:	4100 g
model:	BP-3400

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States