

Precision Balances 0.01g BP-6100



Description

Precision Balances 0.01g BP-6100 feature weighing capacities of 100 g and readabilities of 0.02g. Our Precision Balances are designed for pharmaceutical, laboratory and regulated weighing in a variety of cell and tissue culture facilities that require the highest accuracy in precision weighing processes.

Denver precision balances are designed for routine weighing applications in your workplace, offering accuracy and repeatability during essential weighing applications in education, laboratory and, industrial sector. Denver precision balances deliver competitive performance at an economical price, featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, these balances are perfectly designed for your workplace.

Standard features include Basic functionality for routine weighing applications. Denver precision balances feature three essential weighing modes, RS232 connectivity for data transfer and storage and internal calibration (in selected models) making them ideal for routine weighing applications.

Designed for uncomplicated operation with easy-to-use display and interface Equipped with an easy-to-read, bright backlit display and a simple user interface, they are incredibly easy to operate, with almost no training required.

Smart design and durable construction Denver precision balances have a small footprint which saves on benchtop space while providing a large weighing surface. They are durably constructed, and feature a stainless-steel pan to withstand day-to-day use in the workplace.

Technical:

Model	BP-6100	BP-6200	BP-6300	BP-6400	BP-6500	BP-6600	BP-6700
Capacity	0 to 100 g	0 to 200 g	0 to 300 g	0 to 500 g	0 to 600 g	0 to 1000 g	0 to 2000 g
Resolution	0.01g						
Repeatability	±0.02 g		±0.01 g	±0.02 g	±0.01 g		
Display	LCD display						
Pan Dimension	125mm						
Material	Base: Al alloy, Platter: SS						
Linearity	±0.02 g		±0.01 g	±0.02 g	±0.01 g		
Calibration	FCC, CE						
Interface	RS232						
Certification	CE						
Stabilization Time	1 to 2 seconds						
Dimension	290x1850x80 mm		280x180x170	290x1850x80 mm	280x180x170 mm		
Weight	2 kg		2.2 kg	2 kg	2.2 kg		

Electric al Requ irement	110V/5 0Hz	250/V6 0Hz	110V/5 0Hz	250/V6 0Hz	110V/5 0Hz	250/V6 0Hz	110V/5 0Hz	250/V6 0Hz	110V/5 0Hz	250/V6 0Hz	110V/5 0Hz	250/V6 0Hz	110V/5 0Hz	250/V6 0Hz
Catalog ue No.	680800 501	680800 502	680801 001	680801 002	680801 501	680801 502	680802 001	680802 002	680802 501	680802 502	680803 001	680803 002	680803 501	680803 502

Shipping:	2 - 3 weeks Delivery.
pan_dimension:	125mm
calibration:	-
reproducibility:	0.02 g
resolution:	0.01g
capacity:	0 to 100 g
model:	BP-6100

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States