Precision Balances 0.01g BP-7400

Description

Precision Balances 0.01g BP-7400 feature weighing capacities of 2000 g, and readabilities of 0.01g. Our Precision Balances are designed for pharmaceutical, laboratory and regulated weighing in a variety of cell and tissue culture facilities that require the highest accuracy in precision weighing processes.
Denver precision balances are designed for routine weighing applications in your workplace, offering accuracy and repeatability during essential weighing applications in education, laboratory and, industrial sector. Denver precision balances deliver competitive performance at an economical price, featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, these balances are perfectly designed for your workplace.
Standard features include Basic functionality for routine weighing applications. Denver precision balances feature three essential weighing modes, RS232 connectivity for data transfer and storage and internal calibration (in selected models) making them ideal for routine weighing applications.
Designed for uncomplicated operation with easy-to-use display and interface Equipped with an easy-to-read, bright backlit display and a simple user interface, they are incredBTy easy to operate, with almost no training required.
Smart design and durable construction Denver precision balances have a small footprint which saves on benchtop space while providing a large weighing surface. They are durably constructed, and feature a stainless-steel pan to withstand day-to-day use in the workplace.

Technical:

Model	BP-7100	BP-7200	BP-7300	BP-7400	BP-7500	BP-7600	BP-7700	BP-7800
Capacity	300 g	320 g	600 g	2000 g	600 g	620 g	1000 g	3000 g
Repeatability	± 0.02 g							
Display	LCD display with backlight and icons							
Resolution	0.01 g							
Pan Dimension	115 mm							
Material	Cast aluminum, static resistant ABS, stainless steel pan							
Linearity Error	± 0.02 g							
Calibration	Calibration with External Weight							
Measuring Parameters	g, ct, lb, oz, ozt, dwt, kg, tmR, GSM, PKT etc(17 units)							
Working Temperature	10 °C to 40 °C							

Interface	Configurable RS 232																		
Certification	FCC, CE																		
Stabilization Time	? 2 sec																		
Dimension	304x204x300 mm																		
Electrical Requirement	110V	240V	110V	240V	110V	240V	110V	240V	110V	240V	110V	240V	110V	240V		110V	240V		
Catalogue No.	68085050 1	680850502	68085100 1	68085100 2	68085150 1	68085150 2	68085200 1	68085200 2	68085250 1	68085250 2	68085300 1	68085300 2	68085350 1	680853502		68085400 1	68085400 2		
Model	BP-7100	BP-7200	BP-7300	BP-7400	BP-7500	BP-7600	BP-7700	BP-7800											
Capacity	300 g	320 g	600 g	2000 g	600 g	620 g	1000 g	3000 g											
Repeatability	± 0.02 g																		
Display	LCD display with backlight and icons																		
Resolution	0.01 g																		
Pan Dimension	115 mm																		
Material	Cast aluminum, static resistant ABS, stainless steel pan																		
Linearity Error	± 0.02 g																		
Calibration	Calibration with External Weight																		
Measuring Parameters	g, ct, lb, oz, ozt, dwt, kg, tmR, GSM, PKT etc(17 units)																		
Working Temper	10 °C to 40 °C																		

ature																
Interface	Configurable RS 232															
Certification	FCC, CE															
Stabilization Time	? 2 sec															
Dimension	304x204x300 mm															
Electrical Requirement	110V	240V	110V	240V	110V	240V	110V	240V	110V	240V	110V	240V	110V	240V	110V	240V
Catalogue No.	68085051	680850502	68085101	68085102	68085151	68085152	68085201	68085202	68085251	68085252	68085301	68085302	68085351	680853502	68085401	68085402

Shipping:	2 - 3 weeks Delivery.
pan_dimension:	115 mm
calibration:	-
reproducibility:	0.02 g
resolution:	0.01 g
capacity:	2000 g
model:	BP-7400

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States