

Top-loading Balances 0.1g BT-2300



Description

Top-loading Balances 0.1g BT-2300 feature weighing capacities of 1000 g, and readabilities of 0.1g/0.01g. Some applications include weighing, counting, check weighing, weighing under unstable conditions, peak hold and percentage (%).

Denver top-loading balances are designed for routine weighing applications in your workplace, offering accuracy and repeatability during essential weighing applications in education, laboratory and, industrial sector. It delivers competitive performance at an economical price, featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, these balances are perfectly designed for your workplace.

Standard features include Basic functionality for routine weighing applications. Equipped with three essential weighing modes, RS232 connectivity for data transfer and storage and internal calibration (in selected models) making them ideal for routine weighing applications.

Designed for uncomplicated operation with easy-to-use display and interface Equipped with an easy-to-read, bright backlit display and a simple user interface, they are incredibly easy to operate, with almost no training required.

Smart design and durable construction Denver top pan balances have a small footprint which saves on benchtop space while providing a large weighing surface. They are durably constructed, and feature a stainless-steel pan to withstand day-to-day use in the workplace.

Technical:

Model	BT-2100		BT-2200		BT-2300		BT-2400			
Capacity	200 g		600 g		1000 g		1200 g			
Resolution	0.1g/0.01g									
Repeatability	±0.2g/±0.02g									
Display	LED									
Pan Dimension	125 mm									
Material	Aluminum Alloy die cast base and mains and Stainless steel pan									
Measuring Parameters	Checking Weighing, piece counting function									
Stabilization Time	1.5 seconds									
Dimension	290x1850x80 mm									
Weight	1800 g									
Electrical Requirement	110V	240V AC	110V	240V AC		110V	240V AC		110V	240V AC
Catalogue No.	680950501	680950502	680951001	680951002	680951501		680951502	680952001		680952002

Shipping:	2 - 3 weeks Delivery.
pan_dimension:	125 mm
calibration:	-
reproducibility:	0.2g/0.02g
resolution:	0.1g/0.01g

capacity:	1000 g
model:	BT-2300

Iris Analytical Ltd.

66 W Flagler St #900
Miami, Florida 33130
United States